

Humanoid recognition AI alarm WIFI spherical IP camera

Features:

3 million gun machines and 3 million ball machines, the picture is spliced up and down into 6 million, and the image is clear and exquisite;

Support human shape detection, tracking and capturing;

Support dual light, human shape and intelligence (line mixing, area care, etc.);

Supports wired and wireless network connections, as well as dual-band networking.

Support 2D/3D noise reduction and digital wide dynamic;

Advanced H.264AI video compression technology, ultra-low bit rate, high-definition image quality;

Lightning protection, in accordance with national standard GB/T17626.5 and international standard IEC61000-4-5;

Support ONVIF protocol and access to third-party backend/platform;

Support mobile phone monitoring (iOS, android);

Support a variety of cloud technologies to achieve network penetration, front-end and back-end docking, and push alarm information to mobile phones and other functions;

Technical Parameters

Model	MS-A31-12V
master control	Dual-core 32-bit DSP (232W1), pure hard compression, watchdog
sensor	Two 2 million 1/3.2 " high-performance CMOS sensors
Minimum illumination	Color:0.01Lux @(F1.2,AGC ON); 0 Lux with IR; Black and white:0.001 Lux @ (F1.2,AGC ON),0 Lux with IR
shutter	1/50(1/60)秒至1/10000秒
ocal distance	F1.4*4MM+F1.4*4MM
noise reduction	Support 2D/3D noise reduction
Video format	H.264AI
resolving power	Main resolution: 2304*2592
Frame rate	12 fps
Intelligent	Support human shape detection
Tracking	Support human shape tracking
light source	4+4 infrared+4+4white light Red and blue lights
Light mode	Starlight full color/infrared night vision/dual light warning
Two-way voice	sustain
Cloud storage	sustain
Support	Support NETIP protocol and onvif protocol
network	10M/100M adaptive Ethernet port
Storage interface	Local TF card (up to512G)
Reset key	Support one-click recovery
Wireless	IEEE802.11b, 802.11g, 802.11n
frequency range	2.4 GHz ~ 2.4835 GHz 5.15 ~ 5.25GHz; 5.25 ~ 5.35GHz; 5.47~5.73GHz; 5.735~5.835GHz
power waste	10W
Product size	
Color box size	
temperature	Zero 10 ° C -60 ° C, humidity less than 90% [no condensation]
Power Supply	DC 12V ± 10%
weight	